

Environmental Selections

Environmental selections available are:

NONE
NO ADDED UF
FSC
CONTROLLED FSC

For both Estimating and Detailing, the default environmental selection will remain as NONE.

1.) NONE –

Doors will be manufactured using VTI standard materials and methods of construction. This selection is valid for all door thicknesses and all door types. These doors will not have an on product FSC label.

2.) NO ADDED UF –

Doors will be manufactured with no added urea formaldehyde crossbanding. No Added UF is available on 1 ¾ inch thick Agrifiber, Stave, SCLC, Mineral core, Particleboard, STC-45, and lead lined doors. No Added UF is also available on 1-3/8 inch thick Agrifiber and Particleboard doors. These doors will not have an on product FSC label.

3.) CONTROLLED FSC –

Particleboard, Stave, and SCLC doors will be manufactured with FSC cores, stiles, rails, and crossbanding. Agrifiber doors will be manufactured with FSC stiles, rails, and crossbanding. The following mineral core doors types (5511, 5P11, 5545 and 5P45 with additional blocking) will be manufactured with FSC crossbanding. The following mineral core doors types (5545 and 5P45 without additional blocking) will be manufactured with FSC stiles, rails, and crossbanding. Lead-lined doors will be manufactured with FSC cores, stiles, rails, and crossbanding. Controlled veneer will need to be selected for the face material. Controlled FSC is available on 1-3/4 inch thick doors as well as 1-3/8 inch thick Particleboard and Agrifiber doors. These doors will have an on product FSC label. Controlled FSC is not available for any of the laminate door types.

4.) FSC –

Particleboard (5 ply), Stave, and SCLC doors will be manufactured with FSC cores, stiles, rails, crossbanding, and face material. Particleboard 3 ply doors will be manufactured with FSC cores, stiles, rails, and face material. Agrifiber doors will be manufactured with FSC stiles, rails, crossbanding, and face material. Mineral core door types (1111, 1P11, 5511, 5P11, 5545 and 5P45 and 1345 and 1P45 with additional blocking) will be manufactured with FSC crossbanding and face material. The following mineral core door types (5545 and 5P45 and 1345 and 1P45 without additional blocking) will be manufactured with FSC stiles, rails, crossbanding, and face material. Lead-lined doors will be manufactured with FSC core, stiles, rails, crossbanding, and FSC face material. This FSC selection is available on 1-3/4 inch thick doors as well as 1-3/8 inch thick Particleboard and Agrifiber doors. These doors will have an on product FSC label.

Description	Hard Coded	Long Description
1.) NONE		
2.) NO ADDED UF	NO ADD UF	NO ADDED UF
3.) FSC	FSC	CHAIN OF CUSTODY CODE SW-COC-000736 FSC MIXED 98% CERTIFICATE EXPIRES JUNE 30, 2012.
4.) CONTROLLED FSC	CTRLFSC	CHAIN OF CUSTODY CODE SW-COC-000736 FSC MIXED 97% CERTIFICATE EXPIRES JUNE 30, 2012.

NOTE: CONTROLLED FSC with an Agrifiber door type (909, 9P09, 5509, 5P09) will have a long description of CHAIN OF CUSTODY CODE SW-COC-000736 FSC MIXED 90% CERTIFICATE EXPIRES JUNE 30, 2012.

Here is a list of where each description/field above is displayed or can be found.

Description

VTOL environmental field selection
 Final Order Acknowledgements with detail
 Formal Quotes
 VTOL customer submitted quote (Estimate Summary)
 Quick Quotes
 VTOL customer requested report (Estimate Summary)

Hard Coded

VTOL customer submitted order
 VTOL customer requested detail report

Long Description

Packing Slip
 Invoices