

GENERAL HIGH PRESSURE DECORATIVE LAMINATE DOOR NOTES

- 1. Vertical grade standard (VGS) laminate is the VT standard on 5-ply construction. Horizontal grade standard (HGS) laminate is the VT standard on 3-ply construction.
- 2. VT Industries uses high pressure decorative laminate from leading manufacturers.
- 3. Doors with a gloss finish laminate will carry no warranty on telegraphing, photographing or scratching.
- 4. Protective peel coats on gloss laminates are not removed at factory. VT is not responsible for removal or disposal at jobsite.
- 5. Certain laminate finishes require an upcharge. Please note desired finish at bid time.
- 6. For all doors with different laminate colors on each face:
 - There is a laminate color coordination fee for these doors which varies from job to job, based on specific needs.
 - Advise which color goes on hinge face, which color on stop face and which color on each • edge.
- 7. Doors with 45-, 60- or 90-minute fire ratings cannot use 1/8" (.125) laminate.
- 8. Doors with an HPDL face on one side and a wood veneer face on the other side will carry no warranty or fire label.
- Exterior doors must be noted at time of bid. Exterior doors are not warranted.
- 10. Pairs of 20-minute doors will be provided with fire retardant lock stiles unless an aluminum flat bar astragal (FBA) is specifically called out for at the time of bid.
- 11. Pairs of 45-, 60- & 90-minute doors must be supplied with metal astragals or intumescent. VT standard astragals are NOT mortised into face of door.
- 12. Metal astragals and vision panels are provided with a beige polyester powder coat finish unless otherwise noted at time of bid.
- 13. Watch the terminology used in the specifications. Clearly spell out any unusual wording. The following terms & phrases are examples of items which should receive special attention:
 - "Super Nova" doors
 - Structural Composite Lumber (SCL) or Laminated strand lumber (Timberstrand) •
 - "No through-bolting allowed."
- 14. VT's Customer Service Center does not interpret specifications.
- 15. Customer must provide a physical sample when painted wood stops or edges are required on doors with multi-colored faces.
- 16. Sample request forms are available under Sample Process section of the Order Process Guide or on our Web site at www.vtindustries.com/doors/forms.shtml.

*Contact your Customer Service Representative for information for a list of VT's leading laminate manufacturers.